

Technical data sheet:

SIGA-Wigluv®



Updated on: 11/12/2012

Distributor: SIGA Cover, Inc.

Type of application: durably rainproof and windtight joints on facades and inclined roofs

Instructions for application: see Manual

Construction: vapor permeable special PO film, elastic, impermeable to water, UV-stable, with SIGA acrylic pressure sensitive adhesive

Packaging unit:

Wigluv 60	10 rolls / box
Wigluv 100	6 rolls / box
Wigluv 150	4 rolls / box
Wigluv 230	2 rolls / box

Characteristics:

			Standards	Units	Values
Dimensions		Length / width	Wigluv 60	m / m feet / inch	40 / 0.06 131 / 2.4
			Wigluv 100	m / m feet / inch	25 / 0.10 82 / 3.9
			Wigluv 150	m / m feet / inch	25 / 0.15 82 / 5.9
			Wigluv 230	m / m feet / inch	25 / 0.23 82 / 9.06
Temperature resistance				°F °C	- 40 °F to + 212 °F - 40 °C to + 100 °C
Processing temperature				°F °C	from + 14 °F from - 10 °C
Atmospheric exposure					max. 12 months
Water vapor transmission			ASTM E-96A	US perm	> 1.72
Water resistance			AATCC-127	cm	500
Ageing resistance			high permanent adhesive strength, non-drying and non-embrittling since without caoutchouc, resin or solvent, can reliably and durably absorb structural movements		
Suitability for storage			unlimited store in a cool, dry place in its original box		